

# Cake/chocolate cooling tunnel with cooling rooms

## Features:

Type	Air-cooled / Water-cooled
Weight	150Kg/M
Capacity	100-2000Kg/Hr
Speed	Adjustable 1~15 M/min
Voltage	220V/380V
Power	10-65KW
Tunnel Temp	0~10°C
Material of Frame	Stainless Steel
Material of Belt	White PU Belt (Food industry)
Application	Food Industrial Cooling
Drive Motor	SEW / CPG 1.1~5.5KW
Compressor	BITZER / COPELAND 5~25 Hp
Condenser	BITZER / COPELAND
Warranty	1 Year
Package	Wooden Case
Holding Time	1~60 min
Control Models	PLC & Touch Panel
Working Temp	-10~10 °C
Common Size	W=1150/1450/1750(mm)

## Advantage:

- a. Specializing in this field for more than **10** years, Have been the **Global Supplier** of multinational companies.
- b. Have **own R&D Dept.** & **Production** Equipment.
- c. A number of Practical Patents in the **Energy Saving** and **Environmental Protection**.
- d. CE,TUV, ISO, AQA Certificated.
- e. Nice appearance.
- f. Unique Design for **Easy cleaning** & **Maintenance**.
- g. Various of dimensions, customized is available.
- h. **Precise temperature control** by separated zone used.

## Benefit:

1. Consistency and flexibility.
2. Innovation.
3. Easy Clean and Maintenance.
4. Nice Appearance.
5. Reliability and Service.
6. Energy Saving and Environmental Protection.
7. Precise temperature control.

## Detail Image:



## Package:

Wooden Case will be used if no special requirements.



## Delivery & Payment:

### 1. Delivery Time:

60 working days after receiving payment

### 2. Terms of payment:

50% T/T in advance, the balance shall be paid before the shipment. The above price is based on current exchange rate, if the exchange rate changed 2%, we cannot keep the price.

### 3. Testing & Training (If you need):

The plant layout design, assembling, installation and debugging, start-up and local team training will be Free at no cost. But the buyer should be responsible for the round-trip air

tickets, local transportation, board & lodging, and USD \$ 45/day/person for the pocket money to our technicians.

About Us:

