

# AMC-SL Cooling Water Chiller

## Characteristics

- 1 Easy installation and no need of cooling tower
  - 2 Specations from 5HP-30HP are available
  - 3 Multi-safety protection is adopted to ensure the safety operation of the whole unit
  - 4 Inside wiring, vacuumizing, refrigerant adding and adjusting are finished before shipping
- Application:  
raw material of food, cooling of finished products, medical equipments etc.

## Specifications

| Specifications compressor | cooling capacity | Chilled water pump |            | cooling water |                | Dimensions(mm) |      |      | weight(kg) | Specifications |
|---------------------------|------------------|--------------------|------------|---------------|----------------|----------------|------|------|------------|----------------|
|                           |                  | power (kw)         | flow (t/h) | flow (t/h)    | diameter Inch) | L              | W    | H    |            |                |
| 3SLA                      | 8500             | 0.55               | 4          | 4             | 1              | 1000           | 780  | 880  | 150        | 3SLA           |
| 5SLA                      | 12500            | 0.75               | 5          | 5             | 1              | 1000           | 600  | 1000 | 165        | 5SLA           |
| 8SLA(B)                   | 18900            | 1                  | 8          | 8             | 1              | 1500           | 750  | 1300 | 280        | 8SLA(B)        |
| 10SLA(B)                  | 26530            | 1.5                | 12         | 12            | 1.5            | 1500           | 750  | 1300 | 300        | 10SLA(B)       |
| 12SLA(B)                  | 30500            | 2.2                | 12         | 20            | 2              | 1500           | 750  | 1300 | 320        | 12SLA(B)       |
| 15SLA(B)                  | 34500            | 2.2                | 12         | 22            | 2              | 1500           | 750  | 1300 | 350        | 15SLA(B)       |
| 20SLA(B)                  | 52460            | 2.2                | 12         | 22            | 2.5            | 1500           | 750  | 1400 | 450        | 20SLA(B)       |
| 25SLA(B)                  | 58996            | 3                  | 16         | 22            | 2.5            | 2000           | 750  | 1400 | 500        | 25SLA(B)       |
| 30SLA(B)                  | 78690            | 3                  | 16         | 35            | 2.5            | 2500           | 900  | 1500 | 530        | 30SLA(B)       |
| 45SLA(B)                  | 114000           | 3.75               | 16         | 35            | 2.5            | 2500           | 900  | 1500 | 770        | 45SLA(B)       |
| 50SLA(B)                  | 117992           | 3.75               | 22         | 40            | 3              | 3000           | 1000 | 1500 | 1010       | 50SLA(B)       |
| 60SLA(B)                  | 152000           | 3.75               | 22         | 40            | 3              | 3000           | 1000 | 1060 | 1060       | 60SLA(B)       |



**AMC**





**AMC**

